



HDMP 10-S1



SELECTION CHART


PUMP SPEED - 100 SPM (NOMINAL) GEAR RATIO 15:1 MOTOR 1440 RPM			MODEL	PLUNGER Dia mm	Max. Pr. Kg/cm ²	PUMP SPEED - 185 SPM (NOMINAL) GEAR RATIO 8:1 MOTOR 1440 RPM		
Cap. LPH	Suc. Del. mmNB/BSP	Motor k.w				Cap. LPH	Suc. Del. mmNB/BSP	Motor k.w
17	15	0.75	HD MP10 S1	26	30	53	15	0.75
24	15			30	28	71	15	
48	15			32	24	80	15	
68	15			40	15	125	15	
82	15			44	12	152	15	

MOC CHART

Sr.No.	Description	MOC	Sr.No.	Description	MOC
1	Plunger	EN 8	4	NRV Sealing Ring	PTFE
2	Liquid Head	SS304, SS316, alloy20,P.P.,PVC,PTFE	5	NRV Balls	SS, PTFE, Ceramic
3	Non Return	SS304, SS316, alloy20,P.P.,PVC,PTFE			

FEATURES

- Multiple head pumps with common drive for mixing two or more liquid in a desired ratio. The ratio can be easily reset.
- The design & Performance of MM Series Pumps conforms to API675.



DIMENSIONS IN MM

A	A1	B	C	D	E	F	
130	130	180	250	200	340	170	
G	H	I	J	K	L	M	N
330	Ø150	10	15	75	400	30	350

WEIGHT (App) : 50 KG.

PACKING SIZE : 19 x 19 x 16 Inches

MINIMAX PUMPS PVT. LTD

AN ISO 9001:2008 COMPANY

PLOT NO. 69, SICOF, 328, MIDC, SATPUR, NASHIK - 422007.
 MAHARASHTRA, INDIA. Tel. : +91-253- 6649383, Mobile :
 09130022891, 9130022894, 9130022893 E-mail :
 minimaxpumps Pvt Ltd@gmail.com Website :
www.dosingpumpsindia.co.in / www.minimaxdosing.co.in



ISO 9001 2008